



5		6	7	8		
I.MOD	I.A.	DESCRIZIONE	DATA	N.MOD.	FIRMA	RIF. EST.
	01	Aggiornate opere murarie con rispettivi loghi.	17/01/17	SM	RG	
	02	Aggiunta l'alternativa cod. 250092670.	09/10/2017	SM	FR	

TRIM ACCURATELY		NOT DIMENSIONED CHAMFERS SM 1x45°		NOT DIMENSIONED CONNECTORS R=1	
 TEST & SERVICE EQUIPMENT		DENOMINATION <b>PIT WORKS FOR BRAKE TESTING UNITS SPRT102/4/5/6/7 P</b>			DATE <b>14/04/16</b>
					SCALE
MATERIAL		TREATMENT			ENG. <b>RG</b>
RAW MATERIAL		FINISHING			APPROVED -
FORMAT <b>A3 ISO 5457</b>		GENERAL TOLERANCES :UNI EN 22768-1 mk			PROJECT
		MACHINE		SHEET <b>1</b>	WEIGHT kg
		GROUP		TOT. PAGES <b>1</b>	REVISION <b>02</b>

RECOMMENDED CHARACTERISTICS OF THE POWER SUPPLY LINE:

Main electric board:

- Minimum required power: 15Kw - 380V 3-phase + neutral
- Magnetothermal switch and differential: 25A

Line from the main electric board to the control unit board:

- Section of the flexible cable 3-phase + neutral + ground: 5x4mm2
- Leave minimum 2m of cable out of the cables well A to connect the equipment